







|  |      | RWISE SP<br>ARE IN IN | 'ECIFIED:<br>NCHES | TOLERANCES:<br>X.XX= ±0.13 | ST/   | -4    | 21700        | T M  |
|--|------|-----------------------|--------------------|----------------------------|---|-------|--------------|------|
|  | NAME | SIGN                  | DATE               | X.XXX= ±0.015              | The Global Source for Stainless Steel Tools |       |              |      |
| DRAWN<br>APPV'D  | A.T. |                       | 01.21.19           | X.XXXX= -0.0010            |   |       |              |      |
| MATERIAL: SHAFT: 465 MAGNETIC S.S.   |      |                       |                    |                            | TITLE:                                      |       |              |      |
| HEX BIT: 316 NON-MAGNETIC S.S.   |      |                       |                    |                            | 1.5MM BALL X 2.00" OAL, 1/4" POWER HEX BIT  |       |              |      |
| WELD: 316 NON-MAGNETIC S.S.  |      |                       |                    |                            |   |       |              |      |
| THIS DRAWING IS THE PROPERTY OF STERITOOL, INC. ANY<br>REPRODUCTIONS OR MODIFICATIONS OF THIS DRAWING OR |      |                       |                    |                            | PART NO.                                    | 13064 |              | REV: |
| ITS CONTENTS WITHOUT THE CONSENT OF STE<br>PROHIBITED.   |      |                       |                    | STERITOOL, INC. IS         | SCALE: 3:1                                  |       | Sheet 1 of 1 | Α    |